an illumination device provided to an opposite side of the liquid crystal display panel in relation to an observation side that illuminates the liquid crystal display panel with illumination light;

a transflective layer disposed on the opposite side of the liquid crystals in relation to the observation side with a transmissive portion that transmits the illumination light formed thereto, the transmissive portion being formed such that a first dimension of a transmissive area corresponding to the transmissive portion of least at one sub-pixel out of the plurality of sub-pixels and a second dimension of a transmissive area corresponding to the transmissive portion at another sub-pixel, differ; and

a color filter provided corresponding to each of the sub-pixels that transmits light of a wavelength corresponding to a color of each sub-pixel.

- 2. (Amended) The liquid crystal display according to Claim 1, the dimension of the transmissive area at each sub-pixel being a dimension according to spectral properties of the illumination light.
- 3. (Amended) The liquid crystal display according to Claim 2, the dimension of the transmissive area at each sub-pixel being a dimension according to the luminance of a wavelength of the illumination light corresponding to a color of the sub-pixel.
- 4. (Amended) The liquid crystal display according to Claim 3, the dimension of the transmissive area at a sub-pixel of a color corresponding to a wavelength of the illumination light with great luminance being smaller than the dimension of the transmissive area at a sub-pixel of a color corresponding to a wavelength of the illumination light with small luminance.
- 5. (Amended) The liquid crystal display according to of Claim 1, the dimension of the transmissive area at each of the sub-pixels differs for each sub-pixel corresponding to a different color.

- 6. (Amended) The liquid crystal display according to Claim 1, the dimension of the transmissive area at each of the sub-pixels differing according to a position of the sub-pixel within a substrate face of the liquid crystal display panel.
- 7. (Amended) The liquid crystal display according to Claim 1, the transmissive portion being an opening portion formed in the transflective layer corresponding to each of the sub-pixels.
- 8. (Amended) The liquid crystal display according to Claim 7, the opening portion comprising opening parts of generally the same dimension that are formed mutually separated for the number according to the dimension of the transmissive area at the subpixels.
- 9. (Amended) The liquid crystal display according to Claim 1, the transflective layer having the transmissive portion formed such that an area along at least one side of a plurality of sides defining each sub-pixel serves as the transmissive area.
- 10. (Amended) A liquid crystal display, serving as a transflective liquid crystal display which performs displaying by switching between a transmissive mode and a reflective mode, comprising:

a liquid crystal layer sandwiched between an upper substrate and a lower substrate opposing one another;

a transflective layer which has a transmissive area that transmits light and a reflective area that reflects incident light from an upper substrate side, and which is disposed on an inner side of the lower substrate;

a color filter disposed on an upper side of the transflective layer, upon which a plurality of pigment layers with different colors according to each of sub-pixels forming a display area are arrayed; and

an illumination device disposed on an outer side of the lower substrate,

the pigment layers being formed over an entirety of an area overlapping the transmissive area in a planar manner and an area overlapping the reflective area in a planar manner, and at least one color pigment layer being formed only at a part of an area overlapping the reflective area in a planar manner,

and a dimension of a pigment layer formation area, where the pigment layers are formed, being formed so as to be different between at least one color pigment layer out of the plurality of pigment layers of differing colors; and another color pigment layer.

- 11. (Amended) The liquid crystal display according to Claim 10, the pigment layers comprising a red layer, a green layer, and a blue layer, and the dimension of the pigment layer formation area being formed so as to be smaller for the green layer than for the red layer and blue layer.
- 12. (Amended) The liquid crystal display according to Claim 10, further comprising a transparent film for smoothing a step between the pigment layer formation area and the area where the pigment layers are not provided.
- 13. (Amended) The liquid crystal display according to Claim 10, the transmissive area being formed by the transflective layer being opened in a window-like manner.
- 14. (Amended) The liquid crystal display according to Claim 10, band-shaped transparent electrodes being disposed on the inner side of the lower substrate, and the transmissive area of a band shape being formed in the transflective layer by having a transparent electrode pattern width that is formed wider than a transflective layer pattern width.
- 15. (Amended) The liquid crystal display according to Claim 11, the transflective layer being formed of at least one of aluminum and an aluminum alloy, and the pigment layer containing the blue layer, and the dimension of the pigment layer formation area being provided so as to be smaller for the blue layer than for the red layer.

- 16. (Amended) The liquid crystal display according to Claim 11, the transflective layer being formed of at least one of silver and a silver alloy, and the pigment layer containing the red layer and the blue layer, and the dimension of the pigment layer formation area being provided so as to be smaller for the red layer than for the blue layer.
- 17. (Amended) The liquid crystal display according to Claim 10, the color properties of the color filter being adjusted by changing the dimension of the pigment layer formation area.
- 18. (Amended) A liquid crystal display, serving as a transflective liquid crystal display which performs displaying by switching between a transmissive mode and a reflective mode, comprising:

a liquid crystal display panel formed of a liquid crystal layer sandwiched between an upper substrate and lower substrate opposing each other, and including pixels that have a plurality of sub-pixels each corresponding to different colors and form a display area; and

an illumination device/provided to an opposite side of the liquid crystal display panel in relation to an observation side that illuminates the liquid crystal display panel with illumination light;

a transflective layer disposed on an opposite side of the liquid crystal layer in relation to the observation side; and

a color filter provided above the transflective layer with a plurality of pigment layers of different colors corresponding to each of the sub-pixels arrayed thereupon, that transmits light of a wavelength corresponding to a color of the sub-pixel,

a transmissive portion that transmits the illumination light being formed on the transflective layer that includes a transmissive area that transmits light and a reflective area that reflects incident light from an upper substrate side,

and the transmissive portion being formed such that a first dimension of the transmissive area corresponding to the transmissive portion at least at one sub-pixel of the plurality of sub-pixels and a second dimension of the transmissive area corresponding to the transmissive portion at another sub-pixel, differ,

and pigment layers of each color are formed over an entirety of an area overlapping the transmissive area in a planar manner and an area overlapping the reflective area in a planar manner, and at least one color pigment layer being formed only at a part of an area overlapping the reflective area in a planar manner,

and a dimension of a pigment layer non-formation area where the pigment layer is not formed at least at one sub-pixel of the plurality of sub-pixels and the dimension of a pigment layer non-formation area at another sub-pixel, differ.

19. (Amended) An electronic apparatus, comprising the liquid crystal display according to Claim 1.

Please add new claim 20 as follows:

m

Ħ

--20. An electronic apparatus, comprising the liquid crystal display according to claim 10.--

REMARKS

Claims 1-20 are pending in this application. By this Preliminary Amendment, the abstract, specification and claims are amended, and new claim 20 is added. No new matter is added.

The attached Appendix includes marked-up copies of the substitute specification (37 C.F.R. §1.125(b)(2)) and claims (37 C.F.R. §1.121(c)(1)(ii)).